

Pressure Regulator Product Line

Utility Service and Industrial Appliance Regulators



| <u>Model</u> | <u>Available</u> <u>Versions</u> | Outlet Pressure Range | <u>Available</u> Valve Bodies | <u>Max. Inlet</u> <u>Pressure</u> | <u>Max. Capacity</u> (Natural Gas) | <u> </u> |
|--------------|---|--------------------------|--|--------------------------------------|---------------------------------------|----------|
| B42 | R, N | 5 in. wc to 5 psig | 1/2", 3/4", 1", 1-1/4" NPT | 125 psig | 2,500 scfh | - |
| B58 | R, N | 5 in. wc to 2.5 psig | 1/2", 3/4", 1", 1-1/4" NPT | 125 psig | 2,500 scfh | |
| B57 | R, N | 5 in. wc to 2.5 psig | 1/2", 3/4", 1", 1-1/4" NPT | 125 psig | 2,500 scfh | 1 |
| B31 | r, n, imn, imr, imrv | 4 in. wc to 2.5 psig | 3/4", 1", 1-1/4" NPT | 125 psig | 3,000 scfh | |
| B531 | r, n, imn, imr, imrv | 5 in. wc to 2 psig | 3/4", 1", 1-1/4" INLET; 3/4", 1-1/4", 1-1/2", 1- 3/4", 2" OUTLET (NPT) | 125 psig | 5,000 scfh | |
| B34S | R, N | 4 in. wc to 2 psig | 1-1/4", 1-1/2", 2" NPT 2" FL, 3" FL (125 Class) | 125 psig | 7,500 scfh | |
| B34 | r, n, m, d, imr, Imrv, imn | 5 in. wc to 5 psig | 1-1/4", 1-1/2", 2" NPT 2" FL, 3" FL (125 Class) | 125 psig | 15,000 scfh | |
| B38 | r, n, m, d, imr, Imrv, imn | 5 in. wc to 5 psig | 1-1/2", 2" NPT 2" FL, 3" FL (125 Class) | 125 psig | 20,000 scfh | |
| B838 | r, n, m, d, imr, Imrv, imn | 5 in. wc to 5 psig | 2" x 2" NPT, 2" x 2" FL, 2" x 3" FL, 2" x 4" FL (125 Class) | 125 psig | 50,000 scfh | |
| RB1700 | Ν, Μ | 7 in. wc to 36 psig | 1-1/2" NPT | 230 psig | 100,000 scfh | |
| RB4000 | N, M | 4 in. wc to 30 psig | 2" FL, 3" FL (150 Class RF) | 275 psig | 600,000 scfh | - |
| baded (Fix | ed Factor Billing | g) Regulators | , | | | |
| CL31 | Pilots: R, N Options: IM, IMV | 1 to 20 psig | 3/4", 1", 1-1/4" NPT | 125 psig | 4,000 scfh | |
| CL231 | Pilots: R, N | 1 to 20 psig | 1-1/4", 1-1/2", 2" NPT 2"FL, 3"FL (125 Class) | 125 psig | 7,500 scfh | 1 |
| CL34 | Pilots: -1, -2 Options: M, IM, IMV, D | 5 in. w.c. to 60 psig | 1-1/4", 1-1/2", 2" NPT 2" FL, 3" FL (125 Class) | 150 psig | 40,000 scfh | A STATE |
| CL38 | Pilots: -1, -2 Options: M, IM, IMV, D | 5 in. w.c. to 30 psig | 1-1/2", 2" NPT 2"FL, 3"FL (125 Class) | 150 psig | 60,000 scfh | 6 |
| CL838 | Pilots: -1, -2 Options: M, IM, IMV, D | 5 in. w.c. to 30 psig | 2"x2" NPT, 2" FL 2"x3" FL, 2"x4" FL (125 Class) | 150 psig | 100,000 scfh | 2 |
| ure (Field (| Cut) Regulators | | | | | |
| B35 | R, N, M | 5 to 150 psig | 3/4", 1" NPT | 1,000 psig | 20,000 scfh | |
| D30 | rs, in, ivi | o to Too heið | 3/4 , I NPT | i,uuu psig | 20,000 SCIII | 2 |