


# Eclipse ThermJet

## Burners



Model TJ0040

Version 2

Parameter	Burner Velocity	Model TJ0040	
Maximum Input BTU/hr (kW)	Medium & High Velocity	400,000 (117)	
Minimum Input, On-Ratio BTU/hr (kW)	Medium & High Velocity	40,000 (11.7)	
Minimum Input, Fixed Air BTU/hr (kW)	Medium & High Velocity	10,000 (2.9)	
Gas Inlet Pressure Required "w.c. (mbar) Fuel Pressure at Gas Inlet (Tap "B" - see page 3)	High Velocity	Natural Gas	12.0 (29.9)
		Propane	13.0 (32.4)
		Butane	12.0 (29.9)
	Medium Velocity	Natural Gas	5.5 (13.7)
		Propane	5.5 (13.7)
		Butane	5.0 (12.5)
Air Inlet Pressure Required "w.c. (mbar) 15% Excess Air at Maximum Input (Tap "A" - see page 3)	High Velocity	Natural Gas	15.5 (38.6)
		Propane	17.0 (42.3)
		Butane	17.0 (42.3)
	Medium Velocity	Natural Gas	9.0 (22.4)
		Propane	9.5 (23.7)
		Butane	9.5 (23.7)
High Fire Flame Length Inches (mm) (Measured from End of Combustor)	High Velocity	Natural Gas	14.0 (356)
		Propane	17.0 (432)
		Butane	17.0 (432)
	Medium Velocity	Natural Gas	18.0 (457)
		Propane	19.0 (483)
		Butane	19.0 (483)
Maximum Flame Velocity ft/s (m/s) 15% Excess Air at Maximum Input	High Velocity	500 (152.4)	
	Medium Velocity	250 (76.2)	
Maximum Combustion Air Temperature	300°F (149°C). For higher temperatures, use TJPCA (Data 206).		
Flame Detection	UV scanners available for all combustors. Flamerod available for all combustors and operating temperatures of up to 2,200°F (1,204°C).		
Fuel	Natural gas, propane, or butane. For any other mixed gas, contact Eclipse for orifice sizing.		
Approvals			

- All information is based on laboratory testing in neutral (0.0" w.c.) pressure chamber. Different chamber size and conditions may affect the data.
- All information is based on standard combustor design. Changes in combustor will alter performance and pressures.
- All inputs based upon gross calorific values.
- Eclipse reserves the right to change the construction and/or configuration of our products at any time without being obliged to adjust earlier supplies accordingly.
- Plumbing of air and gas will affect accuracy of orifice readings. All information is based on generally acceptable air and gas piping practices.

## Performance Graphs





Correction factor for medium velocity combustor is 1.20.  
Emissions data based on on-ratio control, firing 15% excess air, corrected to 3% O<sub>2</sub>.


Emissions from the burner are influenced by:

- Fuel type
- Combustion air temperature
- Firing rate
- Chamber conditions
- Percent of excess air


For estimates of other emissions, contact Eclipse.



## Dimensions in inches (mm)




Burner weight less combustor: 21.6 lbs (9.8 kg)



## Combustor


Exhaust Outlet Diameter: High Velocity: Ø1.65 (42)  
Medium Velocity: Ø2.36 (60)



### Alloy Tube (AISI 310)

Weight: 2.1 lbs (0.95 kg)


Maximum Chamber Temp: 1,750°F (950°C)



### Silicon Carbide Tube

Weight: 3.6 lbs (1.63 kg)

Maximum Chamber Temp: 2,500°F (1371°C)



### Refractory Block (w/330 SS wrapper)

Weight: 14 lbs (6.35 kg)

Maximum Chamber Temp: 2,800°F (1538°C)



**Offered By:**

Power Equipment Company  
2011 Williamsburg Road  
Richmond, Virginia 23231  
Phone (804) 236-3800  
Fax (804) 236-3882

---

[www.peconet.com](http://www.peconet.com)