

# Injector Selection Table for Mixed Nat.—Mfd. Gas

Gas at 15 Lbs. Pressure; Approximate Mixture Pressure of 1.8" w.c.\*;  
800 B.T.U.; .55 Specific Gravity; 8.0 Air-Gas Ratio

Based on 100% Air Entrainment thru Injector

Capacity CF/HR at 15 Lbs.	Catalog Number  Injectors	Suggested burner area in square inches when using various types of burners at coefficient of discharge shown				100% Coefficient Discharge Burner
		Walltites 125%	Drilled Round Nose 87%	Sticktite or Ferrofix 75%	Blast Tips 60%	
25	H4 —70	.081	.113	.131	.164	.0985
50	H44 —61	.153	.218	.255	.318	.191
75	H44 — $\frac{3}{64}$	.228	.328	.38	.465	.285
100	H54 —54	.292	.42	.49	.609	.366
125	H54 —53	.356	.51	.595	.740	.445
150	H54 —51	.445	.63	.743	.925	.556
175	H65 —49	.536	.765	.89	1.112	.668
200	H65 — $\frac{5}{64}$	.61	.88	1.02	1.272	.765
250	H86 —44	.735	1.06	1.23	1.530	.92
300	H86 —42	.88	1.28	1.47	1.830	1.10
350	H86 —38	1.03	1.48	1.72	2.15	1.29
400	H108 — $\frac{7}{64}$	1.20	1.72	2.00	2.50	1.5
450	H108 —32	1.34	1.93	2.24	2.80	1.68
500	H108 —31	1.44	2.07	2.40	3.00	1.80
550	H108 — $\frac{1}{8}$	1.57	2.26	2.62	3.26	1.96
600	H1210—29	1.84	2.64	3.07	3.83	2.3
650	H1210—28	1.97	2.83	3.28	4.10	2.46
700	H1210—27	2.08	3.0	3.47	4.24	2.6
750	H1210—26	2.20	3.17	3.68	4.60	2.76
800	H1210—23	2.36	3.40	3.94	4.93	2.96
850	H1210—21	2.52	3.62	4.20	5.25	3.15
900	H1612—19	2.77	3.96	4.59	5.73	3.44
950	H1612—18	2.88	4.12	4.80	6.00	3.60
1000	H1612—17	3.00	4.32	5.02	6.25	3.76
1100	H1612—15	3.23	4.65	5.39	6.73	4.04
1200	H1612—12	3.57	5.12	5.95	7.43	4.46
1300	H1612—9	3.84	5.52	6.40	8.00	4.8
1400	H1612— $\frac{13}{64}$	4.12	5.91	6.87	8.60	5.15
1600	H2016— $\frac{7}{32}$	4.76	6.85	7.95	9.95	5.96
1800	H2016—1	5.2	7.45	8.65	10.80	6.50
2000	H2016—B	5.64	8.10	9.40	11.70	7.05
2250	H2016—F	6.6	9.5	11.00	13.70	8.25
2500	H2420—I	7.35	10.6	12.30	15.80	9.20
2750	H2420— $\frac{9}{32}$	7.85	11.3	13.18	16.40	9.85
3000	H2420—M	8.65	12.5	14.45	18.10	10.85
3500	H2420—P	10.4	14.9	17.35	21.70	13.00
4000	H2420— $\frac{11}{32}$	11.85	17.0	19.75	24.60	14.80
4500	H2420—U	13.6	19.5	22.7	28.30	17.00
5000	H2420— $\frac{25}{64}$	15.2	21.8	25.3	31.70	19.00

\*Mixture Pressure:—The Mixture Pressure that can be developed will vary depending on piping conditions and draft and will vary directly with changes in Gas Pressure.

## CORRECTION FACTORS FOR CAPACITIES AT OTHER THAN 15 LBS. PRESSURE

Pounds Pressure.....	1	2	3	4	5	6	7	8	9	10	11	12	13
Correction Factor.....	.268	.365	.447	.515	.578	.633	.683	.73	.775	.815	.855	.895	.930
Pounds Pressure.....	14	15	16	17	18	19	20	21	22	23	24	25	
Correction Factor.....	.965	1.00	1.03	1.065	1.095	1.125	1.155	1.182	1.211	1.24	1.265	1.29	



**ECLIPSE COMBUSTION**



**Offered By:**

Power Equipment Company  
2011 Williamsburg Road  
Richmond, Virginia 23231  
Phone (804) 236-3800  
Fax (804) 236-3882

---

[www.peconet.com](http://www.peconet.com)